









SITE NOTES

- Advance signs to be placed on all approaches to works.
- Exact sign position to be determined on site. Conflicting permanent signs to be obscured for duration of works.
- Exact site access/egress to be determined on site and signed acordingly.
- The optimum lane width for all classes of vehicles is 3.3m. this may be reduced to a minimum of 3m. below this, HGV's and buses must be marshaled past the works. The absolute minimum lane width, if only cars and light vehicles are present, is 2.5m.
- 5) TTM operative present on-site to coordinate safe site entrance/exit, safe crossing of pedestrians by implementing an all stop when required.
- 6) All works to be carried out in accordance with Chapter 8 of the Traffic Signs Manual (2019 Edition) and Temporary Traffic Management Operations Guidance
- 7) Access to residents/businesses to be maintained at all times. Contractor to notify affected residents in advance of any restrictions.



This drawing is the property of Road Control Services Ltd. The design information contained herein is strictly confidential. This document is no to be used, reproduced, disclosed or circulated in whole or in part

Kilsaran ideas taking shape

CLIENT

DESIGN PARAMETE	RS	Speed Limit 80	Road Classification
Advance Warning Signage		kah	2(i) 1 ype b <12hours
Sign size	600mm	Cones	
Sign Visibility	90m	Cone Height	750mm
Number of Signs	3	Taper Spacing	3m
Cumulative Distance	360m	Longitudinal Spacing	12m
Distance between Advance Warnin	¹ 9 120m	Safety Zones	
Signs		Longitudinal	45m
Taper		Lateral	1.2m
Lane Taper Rate	N/A	Lanes	
Hard Shoulder Taper Rate	N/A	Lane Width	3.0m

LEGEND Works Area Traffic sign Traffic cones Local Access Diversion Route A

GENERAL NOTES JAI information contained in this drawing (including digital data) shoul checked and verified prior to any stage of construction;
2) AI works are to be carried out in accordance with local authority requirements and are to be included in the site-specific safety & health 3) Site inspections and maintenance of the traffic management layout i be agreed with local authority to ensure the safety and integrity of the design: design;
4) Contractor to carry out a site risk assessment prior to the installation any traffic management plan to ensure that conditions reflect those considered for design post submission;
5) Contractor shall be responsible for the provision of ramp access at change in road surface level where traffic runs on a temporary surface Diversion Route B

for pedestrian/cycle ramps where footpath/cycle-ways have a level discontinuity as per result of the works.

	Rev	Date	Details	Drn	Chk	App	Drn	DJ	Project		
ould be							Chk	SD		R442-2 Millgrove Bra	
lth plan;							Арр	DH		Co. Offaly	
ut is to e							Date	11-04-2024 Tit	Title		
on of										TEMPORARY	
0.1.0.							Scale	NTS @A3		TRAFFIC MANAGI	
it any										DIVERSION ROL	
ce, and							Stage				
							CONSTRUCTION	Drawing I	No C25002_03_002		

R442-2 Millgrove Bracknagh, Co. Offaly **TEMPORARY** TRAFFIC MANAGEMENT **DIVERSION ROUTE**

Rev 0